

Product Information Sheet according to (EU) No 65/2014

Trade Mark	AEG
Model	GDG966AB 942022759
Annual Energy Consumption (kWh/year)	26.1
Energy Efficiency class	A++
Fluid Dynamic Efficiency	40.3
Fluid Dynamic Efficiency class	A
Lighting Efficiency (lux/W)	63.83
Lighting Efficiency class	A
Grease Filtering Efficiency	85.1
Grease Filtering Efficiency class	B
Air flow at minimum and maximum speed in normal use (m3/h)	200/400
Air flow at intensive or boost setting (m3/h)	680
Airborne acoustical A-weighted sound power emissions at minimum and maximum speed in normal use (dB(A))	40/54
Airborne acoustical A-weighted sound power emissions at intensive or boost setting (dB(A))	66
Power consumption in standby mode (W)	0
Power consumption in off mode (W)	0.49

Product information according to Commission regulation (EU) No 66/2014

Attribute Name	Symbol	Value	Unit
Model Denomination		GDG966AB 942022759	
Annual Energy Consumption	AEC _{hood}	26.1	kwh/a
Time increase factor	f	0.5	
Fluid Dynamic Efficiency	FDE _{hood}	40.3	
Energy Efficiency Index	EEl _{hood}	33.2	
Measured air flow rate at best efficiency point	QBEP	333.3	m3/h
Measured air pressure at best efficiency point	PBEP	459	Pa
Maximum air flow	Q _{max}	680.0	m3/h
Measured electric power input at best efficiency point	WBEP	105.5	W
Nominal power of the lighting system	WL	9.4	W
Average illumination of the lighting system on the cooking surface	E _{middle}	600	lux
Measured power consumption in standby mode	P _s	0	W
Measured power consumption off mode	P _o	0.49	W
Sound power level	LWA	54	dB

EN 61591 - Household range hoods and other cooking fume extractors – Methods for measuring performance

EN 60704-2-13 - Household and similar electrical appliances – Test code for the determination of airborne acoustical noise – Part 2-13: Particular requirements for range hoods

EN 50564 - Electrical and electronic household and office equipment. Measurement of low power consumption

Suggestions for a correct use in order to reduce the environmental impact:

- Switch ON the hood at minimum speed when you start cooking and kept it running for few minutes after cooking is finished.
- Increase the speed only in case of large amount of smoke and vapour and use boost speed(s) only in extreme situations.
- Replace the charcoal filter(s) when necessary to maintain a good odour reduction efficiency.
- Clean the grease filter(s) when necessary to maintain a good grease filter efficiency.
- Use the maximum diameter of the ducting system indicated in this manual to optimize efficiency and minimize noise.